

sirens

CS200 Series



- Integrated microphone control head
- Adjustable public address volume
- High quality construction
- Rubberised 'soft-touch' handpiece
- Swivel mounting cradle
- Backlit, illuminated buttons
- Easy to use, low-clutter button layout
- 1,2,3 Progressive warning level buttons
- 'Hands-free' control mode
- Radio rebroadcast capability (CS202)
- Manual wail function (CS202)
- 6 channels of relay-switched lighting control with status LEDs (CS202)

Controller Size: 55mm L x 25mm D x 115mm H Weight: 220g



CS201



CS202

- Rugged extruded amplifier housing
- Specially designed convective cooling fins
- Protected against under-voltage, over-voltage, reverse-polarity, supply transients
- Protected against thermal overload + output short circuits
- Designed to drive one or two 11-ohm 100-Watt siren speakers
- Up to 200W siren output power, or 400W with optional slave amplifier unit
- Wide range of supported siren tones
- SOFTSTART™ siren tones
- Vehicle Horn interface (HRT)
- Dedicated Automatic Gain Control (AGC) circuit optimises public address clarity

Amplifier Size: 159mm L x 192mm D x 59mm H Weight: 1780g



CS202 Siren Amplifier

#	MODEL	V	✓	🕒	COMPONENT #
809-015	CS201	12	✓, e	1 year	siren amp 809-930
					controller 809-932
					wiring kit 809-936
					controller cradle 809-938
809-016	CS201	24	✓, e	1 year	siren amp 809-931
					controller 809-932
					wiring kit 809-936
					controller cradle 809-938
809-017	CS202	12	✓, e	1 year	siren amp 809-933
					controller 809-935
					wiring kit 809-939
					controller cradle 809-938
809-018	CS202	24	✓, e	1 year	siren amp 809-934
					controller 809-935
					wiring kit 809-939
					controller cradle 809-938